

# Product Bulletin



Vapor Systems Technologies, Inc.

650 Pleasant Valley Drive  
Springboro, Ohio 45066 (USA)

Toll Free: 1-888-878-4673

Phone: 937-704-9333

Fax: 937-704-9443

www.vsthose.com

## UPDATE:

VST adds more UL Listed  
Low Permeation Hoses to  
Product Offering

**05.29.15**

The VST product portfolio continues to expand with more UL Listed Low Permeation Hoses.

Since August 2014 when VST introduced our first **ENVIRO-LOC™ Low Permeation Dispensing Curb Pump Hose** – our 5/8" ID **Model V58EC** for Conventional applications, we have continued our innovative engineered solutions approach and are now pleased to announce the addition of two more Low Permeation Hose products.

- **Model V34EC** for Conventional applications
- **Model V34EV** for Vapor Assist applications


Both of these new Models meet the UL 330 assembled gasoline dispensing hose requirements, as well as the stringent, reduced low permeation requirements of less than 10 grams/m<sup>2</sup>/day.

### Model V34EC - Conventional

- Hose ID: 3/4"
- Tube: High grade nitrile for oil and fuel resistance
- Hose Reinforcement: Two textile braid with dual helix wire for maximum kink resistance
- Cover: Chlorinated polyethylene for fuel, ozone, and abrasion resistance
- Couplings: 3/4" NPT Male Swivel with VST's unique Lip Seal design


### Model V34EV – Vapor Assist

- Hose ID: 3/4"
- Tube: High grade nitrile for oil and fuel resistance
- Hose Reinforcement: Two textile braid with dual helix wire for maximum kink resistance
- Cover: Chlorinated polyethylene for fuel, ozone, and abrasion resistance
- Couplings: Multiple end style choices: M34 (Swivels), Healy-Style (Swivels), or Balance




Swivel

M34 1.5  
(Metric)



Swivel

1 1/4-18 UNEF  
(Healy-Style)



Rigid

1-7/8-12 UN  
Balance  
Converter  
Coupling

Contact VST or your VST Distributor of choice for details.