



For more information,
Contact: Scott Brown
Office: 937-704-9333
brown@vsthose.com

FOR IMMEDIATE RELEASE

**VST EXPANDS HOSE PRODUCT OFFERING
WITH ENVIRO-LOC™ FLEX FUEL HOSE**

Springboro, Ohio – USA – April 20, 2021 – VST is pleased to announce the latest addition to our fuel dispensing hose product offering. **ENVIRO-LOC™ Flex Fuel** hoses are compatible for applications utilizing ethanol fuel blends ranging from E0 to E85. As the Renewable Fuel Standards (RFS) program in the United States continues to expand with increased volume of ethanol fuel blend options at retail gasoline stations, VST is now positioned to support E15, E25, and E85 applications by offering one hose that is compatible for all of these fueling options.

The **ENVIRO-LOC™ Flex Fuel** Hoses:

- Meet the UL330A Listing requirements
- May be used in applications ranging from E0 to E85 fuel
- Include stainless steel 3/4" rigid male couplings
- Are easily identified with a red and yellow branding stripe



About VST

VST specializes in the development, engineering, manufacturing, and sale of innovative solutions for the retail fuel dispensing industry. Products include hoses, safety breakaways, nozzles, and storage tank pressure management processors. For more information about VST, go to www.vsthose.com.

ENVIRO-LOC™ Flex Fuel Conventional Curb Pump Hose Assemblies



ENVIRO-LOC™ Flex Fuel Conventional Curb Pump Hose Assemblies

are highly engineered fuel delivery hoses designed to meet the stringent UL330A requirements for a wide range of ethanol blended gasolines.

Customer Benefits:

- For use with any blend of ethanol gasoline from E0 to E85 applications
- Light weight assembly
- Easy to handle



Vapor Systems Technologies, Inc.



Striving Towards Sustainability

ENVIRO-LOC™ Flex Fuel Hose Assemblies Specifications



Tube

- High grade Nitrile (NBR) with superior resistance to refined petroleum products (gasoline) inclusive of alcohol rich fuels containing ethanol ranging from E0 through E85

Reinforcement

- Wire braid reinforcement adding kink resistance, high working pressure up to 150 PSI, and superior coupling retention

Cover

- Premium Chlorinated Polyethylene (CPE) for excellent resistance to ozone, UV weathering, cover cracking, and abrasion aimed at promoting longer service life

Couplings

- 3/4" NPT Stainless Steel (Rigid ONLY)

Strain Relievers

- Unique vinyl stress reliever for durability at the hose / coupling interface

Temperature Range

- -40° F to +120° F
Continuous Service

Certifications & Listings

- UL 330A Listed Hose Assemblies

ENVIRO-LOC™ Flex Fuel Hose & Coupling Characteristics

Part No. Series	V34FF
Nom. ID (In.)	3/4"
Nom OD (In.)	1.110"
Braid	Wire
Weight (Lb./Ft.)	.044 lb.
Min. Bend Radius (In.)	4.0"
Coupling End Style	3/4" NPT (Rigid ONLY)

Warranty

- All VST products are covered under the company warranty, which may be found at www.vsthose.com



Vapor Systems Technologies, Inc.

650 Pleasant Valley Drive
Springboro, Ohio 45066 (USA)
Toll Free: 1-888-878-4673

Phone: 937-704-9333
Fax: 937-704-9443
www.vsthose.com